



| NO. | Модель PPro-Light | Мощность |     | Q(m³/h) | Flow rate Q (l/min) |     |     |     |     |     |     |     |     |      |  |  |  |
|-----|-------------------|----------|-----|---------|---------------------|-----|-----|-----|-----|-----|-----|-----|-----|------|--|--|--|
|     |                   | kW       | HP  |         | 0                   | 1.2 | 2.4 | 3.6 | 4.8 | 6.0 | 7.2 | 8.4 | 9.6 | 10.2 |  |  |  |
| A   | PPro-L-V-S 10/2   | 0.75     | 1   | H       | 0                   | 20  | 40  | 60  | 80  | 100 | 120 | 140 | 160 | 170  |  |  |  |
| B   | PPro-L-V-S 10/3   | 1        | 1.4 |         | 25                  | 24  | 23  | 21  | 19  | 16  | 12  | 8   | 3   | 0    |  |  |  |
| C   | PPro-L-V-S 10/4   | 1.35     | 1.8 |         | 38                  | 37  | 35  | 33  | 29  | 25  | 20  | 14  | 7   | 2    |  |  |  |
| D   | PPro-L-V-S 10/5   | 1.65     | 2.2 |         | 52                  | 50  | 48  | 45  | 42  | 36  | 29  | 21  | 12  | 7    |  |  |  |
| E   | PPro-L-V-S 10/6   | 2.1      | 2.8 |         | 65                  | 64  | 61  | 57  | 52  | 45  | 37  | 27  | 16  | 10   |  |  |  |
| F   | PPro-L-V-S 10/7   | 2.4      | 3.2 |         | 78                  | 76  | 73  | 69  | 62  | 54  | 45  | 33  | 20  | 12   |  |  |  |
|     |                   |          |     |         | 92                  | 90  | 87  | 82  | 75  | 65  | 53  | 39  | 23  | 15   |  |  |  |

| Модель PPro-Light | Dn1   | Dn2   | Габаритные размеры (мм) |       |      |     |     |     |     |    | Масса кг |
|-------------------|-------|-------|-------------------------|-------|------|-----|-----|-----|-----|----|----------|
|                   |       |       | h1                      | h2    | H3   | m   | n   | l1  | L2  | s  |          |
| PPro-L-V-S 10/2   | 1.25" | 1.25" | 390                     | 173.5 | 36.5 | 182 | 180 | 122 | 122 | 9  | 14.0     |
| PPro-L-V-S 10/3   | 1.25" | 1.25" | 415                     | 198   | 36.5 | 182 | 180 | 122 | 122 | 9  | 15.2     |
| PPro-L-V-S 10/4   | 1.25" | 1.25" | 465                     | 224   | 36.5 | 200 | 208 | 135 | 135 | 12 | 22.5     |
| PPro-L-V-S 10/5   | 1.25" | 1.25" | 490                     | 248.5 | 36.5 | 200 | 208 | 135 | 135 | 12 | 23.6     |
| PPro-L-V-S 10/6   | 1.25" | 1.25" | 555                     | 275   | 36.5 | 206 | 218 | 135 | 135 | 12 | 28.5     |
| PPro-L-V-S 10/7   | 1.25" | 1.25" | 580                     | 299.5 | 36.5 | 206 | 218 | 135 | 135 | 12 | 32.0     |

